

STRIPPER P 50

Pneumatic dismantling technology



The Stripper P 50

are used in the cable pre-assembling industry ,when cables, ready for further processes are requested. The machines work semi-automatic and are suitable for mass production whenever the outer jacket of the cable has to be removed. The machine is very compact and easy to use.

Function:

The cable beginning is placed into the stripper till the set end stop is reached. Then the foot interruptor is activated. In one step, with help of an installed pneumatic system, the outer jacket is cut and stripped of. The stripped cable can be pulled out. The stripped off jacket falls through a shaft under the machine into a collection tank.

It is very easy to change the stripper blade and cable guide tubes for the suitable stripping length without any tools.

Stripping blades, guide tubes and press blocks are not included in the basic equipment!

Insulation removable length:

STRIPPER P 50 / 100	max.	100 mm	(various 0...100 mm)
STRIPPER P 50 / 500	max:	500 mm	(various 0...500 mm)
STRIPPER P 50 / 1000	max:	1000 mm	(various 0...1000 mm)
STRIPPER P 50 / 1500	max:	1500 mm	(various 0...1500 mm)
STRIPPER P 50/ 2000	max:	2000 mm	(various 0...2000 mm)

Technical data

Basic equipment:		STRIPPER P 50/...		
Part-number:		...		
Delivery time:		6 weeks		
Technical-data:				
- Max. suitable cable diameter:		50 mm		
- Insulation removal length		up to 2000 mm		
Pneumatic:				
- Air pressure		6 bar		
-				
Dimension:				
- Machine		P50/100	P50/500	P50/1000
- item number		10017/200B*	10018/200B*	10019/200B*
- length		750 mm	750 mm	750 mm
- width		800 mm	1750 mm	2600 mm
- height		400 mm	400 mm	400 mm
- Machine		P50/1500	P50/2000	
- item number		10432/200B*	10491/200B*	
- length		750 mm	750 mm	
- width		3600 mm	4100 mm	
- height		400 mm	400 mm	
Available Accessories:				
Blades for stripper	2mm	2,5 mm	----	45 mm 45,5 mm resolution 0,5 mm
Guide tubes	2mm		----	50 mm resolution 1,0 mm
Press block				