

A new era for Reflow.

NEW: HOTFLOW THREE

The Best Reflow Performance in every Aspect:
Quality. Efficiency. Flexibility. Cleaning. Connectivity.



GLOBAL. AHEAD. SUSTAINABLE.



Unique efficiency: the SCPU® motor and control units were developed exclusively for Ersas

With the HOTFLOW THREE, Ersas makes a clear statement for even more quality in soldering. Absolutely unique selling point is the SMART CONVECTION POWER UNIT (SCPU®). The motor and control unit which has been developed exclusively for Ersas ensures an optimized soldering profile and thus an even better soldering result. Single zones can be controlled individually, which enables perfect alignment with the requirements of material and solder paste.

In addition, the SCPU® only consumes the power it actually requires – just like cooling zones and the installed high-performance cooling unit. Absolutely precise injection and monitoring of nitrogen reduces consumption to a minimum.

The result is further enhanced machine availability coupled with maximum productivity, short maintenance times and intuitive operation via ERSASOFT 5 – while keeping consumption low.

Features


- Setting the Benchmark in reflow soldering
- Better performance
- Lower energy consumption
- Sustainable production



Ultimate Soldering Quality.

HOTFLOW THREE

The new, unique SMART CONVECTION POWER UNIT (SCPU®) provides previously unknown soldering quality.



Increasing Productivity. Decreasing Consumption.

HOTFLOW THREE

The precisely coordinated interaction of the new motor and control unit is highly efficient and only consumes energy when required.



Intuitive User Interface and Precise Industry 4.0 Data.

HOTFLOW THREE

Excellent user interface for easy operation and exact process data.



Award-winning ERSASOFT 5 user interface provides easy machine operation and Industry 4.0 data

The HOTFLOW THREE is easy to operate! The industrial PC with touch screen and the intuitive ERSASOFT 5 make the solder program creation and management extremely convenient and future-proof. With the new SMART CONVECTION POWER UNIT, which was exclusively developed for Erska, the HOTFLOW THREE delivers exact process data from every single zone.

Connectivity: Kurtz Erska Connect


With Kurtz Erska GATE, the THREE has Industry 4.0 on board. The gateway ensures reliable, standardised connections between Erska systems and the world outside - including communication between cloud, applications and systems. It processes the obtained measurement data and information and transmits them safely to the Kurtz Erska Cloud or optionally directly to your MES system.

Features

- Maximum usability
- User-friendly industry PC with touch GUI
- Easy MES integration due to standard interfaces
- Real-time data due to standardization
- Traceability (process information)



Intelligent features make machine maintenance super easy



Just like the other components of the Ersas SMART Cleaning system, the SMART CONDENSATION UNIT is quick and easy to access

Ersa THREE stage cleaning system

Another highlight is the innovative cleaning system with SMART ELEMENTS® filter which provides for better handling, longer service life and extended maintenance intervals – or in short: for an increased overall equipment effectiveness (OEE). In the preheating zone, residues are reliably collected, while the SMART PYROLYSIS CLEANER in the peak zone is designed for maximum removal of particle residues. In the cooling zone, the SMART CONDENSATION UNIT is for collection the condensate in a effective way.

Features

- Less maintainance
- Outstanding overall equipment effectiveness
- Higher throughput and performance
- Fast cooling/profile change





It goes on and on and on.

HOTFLOW THREE

Incredible OEE due to the patented, three stage cleaning system with complete accessibility.

Flexibility that fit your needs.

HOTFLOW THREE
Various configurations and optional features always ensure the right system.





Single track or THREE variable dual track conveyor systems are available for HOTFLOW THREE

HOTFLOW THREE, available with 16, 20 or 26 heating zones, offers single track and variable dual track systems for PCB widths of up to 650 mm (single track) or up to 2x 300 mm or 510 mm width (dual track). All versions come with a center support, which can be optionally activated or deactivated.

The HOTFLOW THREE is also convincing when it comes to maintenance – service for the cooling zone and cleaning of the filter systems is easy and carried out via the front.

Features


- Flexible conveyor system
- Nitrogen flexibility





Exemplary visualisation of single or dual track transport and centre support.

Basic configuration Technical Highlights

- SCPU®
 - SMART CONDENSATION UNIT
 - Single Track – max working width 510 mm (650 mm optional)
 - Programmable width adjustment
 - Industry-PC with ERSASOFT 5
- Optimal soldering quality, no matter how complex the assembly, no matter how demanding the components
 - SMART CONVECTION POWER UNIT (SCPU®)
 - Higher productivity with lower/minimized energy consumption
 - Longer maintenance intervals due to innovative three-fold cleaning system
 - SMART ELEMENTS®
 - SMART PYROLYSIS CLEANER
 - SMART CONDENSATION UNIT
- Super maintenance friendly and easy to access components minimize downtimes
 - Intuitive ERSASOFT 5 software platform




HOTFLOW THREE 20






Conveyor systems from single to dual track and with up to two different speeds


Single track: 1 center support and 1 rail variable – working width 510 mm




Dual track: 2 center supports and 2 rails variable



Dual track: 2 center supports and 2 rails variable





Dual track: 2 center supports and 3 rails variable



HOTFLOW THREE 26

HOTFLOW THREE 16
from Summer 2022!



HOTFLOW THREE – Technical Data

Dimensions (basic machine)	HOTFLOW THREE 16	HOTFLOW THREE 20	HOTFLOW THREE 26
Length x Width x Height*	5.65 m x 1.77 m x 1.62 m	6.60 m x 1.77 m x 1.62 m	7.73 m x 1.77 m x 1.62 m
Weight	3.500 kg	4.000 kg	4.500 kg
Process zone			
Heating zones	8 top/bottom	10 top/bottom	13 top/bottom
Heating length	3 m	3.8 m	5.0 m
Cooling zones	3 top/bottom	3 top/bottom	3 top/bottom
Cooling length	1.17 m	1.38 m	1.38 m
Conveyor system			
Conveyor width**	50 - 510 (650) mm	50 - 510 (650) mm	50 - 510 (650) mm
Dual track	2x 50 - 230 (300) mm	2x 50 - 230 (300) mm	2x 50 - 230 (300) mm
Board clearance	+/- 35 mm	+/- 35 mm	+/- 35 mm
Conveyor speed	20 - 200 cm/min	20 - 200 cm/min	20 - 200 cm/min
Conveyor height from floor	830 - 970 mm	830 - 970 mm	830 - 970 mm
Pin-and-chain conveyor	3-4-5 mm	3-4-5 mm	3-4-5 mm
Nitrogen option			
N2 pressure control	5 - 10 bar	5 - 10 bar	5 - 10 bar
Cooling			
Cooling zone	3 Zones with water cooling	3 Zones with water cooling	3 Zones with water cooling
Cooling type	Internal chiller, external or internal chiller and external		
Electrical data			
Power	5 wire system 3 x 400 V, N, PE	5 wire system 3 x 400 V, N, PE	5 wire system 3 x 400 V, N, PE
Frequency	50/60 HZ	50/60 HZ	50/60 HZ
Max. fuse rating	3 x 63 A	3 x 80 A	3 x 100 A
Max power	111 kW	128 kW	156 kW
Reduced power	33 kW	44 kW	55 kW
Exhaust			
Exhaust stacks	2 x 150 mm	2 x 150 mm	2 x 150 mm
Volume per stack	400 m ³ /h	400 m ³ /h	400 m ³ /h
Noise level			
Noise Level	<62 dB (A)	<62 dB (A)	<62 dB (A)

*Conveyor height 830-970mm, **with and without center support

Worldwide presence

With local representatives and our own sales and service offices:

America

Kurtz Ersä, Inc.
1779 Pilgrim Road
Plymouth, WI 53073
USA
Phone +1 920 893 3772
aus den US: 1 800 363 3772
usa@kurtzersa.com
www.ersa.com

Mexico

Kurtz Ersä, S.A. de C.V.
Av. Lopez Mateos Sur Núm. 1450 Int. 7
Col. Las Villas (Plaza las Villas)
Tlajomulco de Zúñiga, Jalisco
C.P. 45643
México
Phone +52 33 15 93 18 63
info-kmx@kurtzersa.com
www.ersa.com

Asia

Kurtz Ersä Asia Ltd.
Unit 03-05, 8th Floor
One Island South
No. 2 Heung Yip Road
Wong Chuk Hang
Hongkong
China
Phone +852 2331 2232
asia@kurtzersa.com
www.ersa.com

China

Ersä Shanghai
Room 720, Tian Xiang Building
No. 1068 Mao Tai Rd.,
Shanghai 200336
China
Phone +86 213126 0818
info-esh@kurtzersa.com
www.ersa.com

Phone +49 9342 800-0

Fax +49 9342 800-127

info@ersa.de

www.ersa.com

Vietnam

Kurtz Ersä Vietnam Company Limited
B916 Road 3, Kizuna 2 Factory Area, Lot
B4-3-7-8, Tan Kim IP, Can Giuoc Dist.
Long An Province, Vietnam
Phone +84 2723 733 682
info-kev@kurtzersa.com
www.ersa.com

India

Kurtz Ersä India
Smart Production Technologies
Private Limited
Plot Nr 18, Survey No. 43
KA 560100 Bangalore
Telefon: +91 973 954 5461
india@kurtzersa.com
www.kurtzersa.com

France

Kurtz Ersä FRANCE
2, Avenue de Wissembourg
67500 Haguenau
France
Phone: +33 6 07 78 01 87
kefrance@kurtzersa.com
www.ersa.com

Ersä GmbH

Leonhard-Karl-Str. 24

97877 Wertheim/Germany

